

A3 colour MFP that is adaptable to your future needs

MX-3051

Office MFP with enhanced security that keeps pace with changing workforce needs



- Print, Copy, Scan, Fax, File
- Paper capacity: Std 650 Max 6,300 sheets
- Print Release function gives users the ability to send and store documents on a main MFP for authentication and print out from any networked MFP
- Shorter warm up time helps reduce energy consumption and improve productivity
- Pages per minute: 30 B/W 30 Colour
- Customisable, tiltable 10.1 inch colour LCD touchscreen with easy UI mode enables intuitive navigation of MFP functions
- Optional single sign-on brings easy access to public cloud storage services
- Multi layered security features

Specifications

GENERAL

Engine speed Colour ppm (A4)	30
Engine speed B/W ppm (A4)	30
Engine speed Colour ppm (A3)	16
Engine speed B/W ppm (A3)	16
Paper size: Min.-Max.	A5 - SRA3
Paper weight (g/m2)	60 - 300
Paper capacity:Std (sheets)	650
Paper capacity: Max. (sheets)	6300
Warm Up Time (sec.)	20
Memory general min/max (GB)	5
Harddisk	STD
Harddisk capacity (GB)	500
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220 - 240V, 50 / 60Hz
Power consumption (kW)	1.84
Dimensions (mm)	608 x 650 x 834
Weight (kg)	79

DOCUMENT FEEDER

Original capacity (sheets)	100
----------------------------	-----

DOCUMENT FILING

Document filing (Standard / Option)	STD
Document filing capacity- main and custom folders (pages)	20000
Document filing capacity- quick file folder (pages)	10000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick file folder, main folder, custom folder (max. 1000)
Confidential storage	.

FAX

Fax (Standard / Option)	OPT
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3 / G3
Transmission time (sec)	2
Modem Speed (bps)	33600 - 2400
Transmission resolution	STD 203.2 x 97.8 dpi / Ultra Fine 406.4 x 391 dpi
Document Size (Min)	A5
Document Size (Max)	A3
Memory (MB)	1024
Grey Scale levels	256
Dial Registration; rapid/speed dial	2000
Broadcast Transmission (max. destinations)	500

WIRELESS LAN

Wireless LAN (Standard / Option)	OPT
Compliant regulation	IEEE802.11n / g / b
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP

COPIER

Original paper size (Max.)	A3
First copy out time Colour (sec.)	6.7
First copy out time B/W (sec.)	4.7
E-sort Std	.
Continuous copy (Max. copies)	9,999
Resolution Scan B/W (dpi)	600 x 600, 600 x 400, 600 x 300
Resolution Scan Colour (dpi)	600 x 600
Resolution Print (dpi)	600 x 600, 9600 x 600
Gradation (equivalent levels) - Colour	256
Zoom range (%)	25 - 400
Preset copy ratios	10

SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	.
Resolution push scan (dpi)	100, 150, 200, 300, 400, 600
Resolution pull scan (dpi)	75, 100, 150, 200, 300, 400, 600, 50 to 9600
File formats	TIFF, PDF, PDF / A, encrypted PDF, compact PDF, JPEG, XPS
Scan destinations Desktop	.
Scan destination FTP, Email	.
Scan destination Network folder	.
Scan destination USB memory	.

PRINTER

Resolution (dpi)	600 x 600, 9600 x 600
Network Printer (Standard / Option)	STD
Interface Std/Opt	USB 2.0,10Base-T / 100Base-TX / 1000Base-T
Supported OS Standard	Windows Server 2008 / 2008R2 / 2012 / 2012R2 / 2016, Windows Vista, Windows 7, 8.1, 10
Supported OS Options	Mac OS X 10.4, 10.5, 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13
Network protocols	TCP / IP (IPv4 and IPv6)
Printing protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP
PDL Std/Opt	STD PCL 6 emulation; OPT Adobe® PostScript® 3™
Available fonts	80 (PCL), 139 (Adobe PostScript 3)

FINISHING

Output Capacity Max.	500 - 3000
Staple Capacity (sheets) Max.	65
Saddle Stitch	OPT
Off-set shifting	STD
Hole punch	OPT

TONER YIELD

Black (pages at 5% coverage)	40000
Cyan (pages at 5% coverage)	24000
Magenta (pages at 5% coverage)	24000
Yellow (pages at 5% coverage)	24000