

A3 black & white MFP that is adaptable to your future needs

MX-M4051

Office MFP with enhanced security that keeps pace with changing workforce needs



- 10.1-inch colour LCD touchscreen with Easy UI mode provides easy, intuitive operation
- Store documents ready for printout from any compatible networked MFP using Print Release*¹
- Direct print Microsoft® Office files from USB drives*²
- OCR allows users to convert scanned documents into editable Microsoft® Office files and searchable PDFs*³
- Single sign-on brings easy access to public cloud storage services*⁴ including Google Drive™, OneDrive® for Business, SharePoint® Online, Box, Dropbox and Cloud Portal Office
- Supports various mobile printing services*⁵
- Sharp Application Portal for downloading firmware and connector updates
- Advanced data protection and access control with SSL validation and whitelisting
- Communication lamps show MFP status
- For large-volume scanned data, a URL can be generated and shared via e-mail
- Support for a secondary LAN (optional) provides simultaneous support for two networks, including a combination of wireless and wired networks
- Replace paper without pausing copy/print jobs

*¹ Can be used from any of five network-connected MFPs. *² Requires optional MX-PU10. This function is enabled via Qualcomm® DirectOffice™ technology. *³ Requires optional MX-EB20. *⁴ Requires optional MX-AMX2. *⁵ Requires optional MX-EB18.

www.sharp.co.uk

www.copierpriceconfigurator.com

CPC
copier price configurator

SHARP
Be Original.

Specifications

GENERAL

Engine speed B/W ppm (A4)	40
Engine speed B/W ppm (A3)	19
Paper size: Min.-Max.	A5 - A3W
Paper weight (g/m2)	60 - 300
Paper capacity:Std (sheets)	650
Paper capacity: Max. (sheets)	6300
Warm Up Time (sec.)	14
Memory general min/max (GB)	5
Harddisk	OPT
Harddisk capacity (GB)	500
Duplex	STD
Power requirements - rated local AC voltage (Hz)	220 - 240V, 50 / 60Hz
Power consumption (kW)	1,84
Dimensions (mm)	608 x 650 x 834
Weight (kg)	64

DOCUMENT FEEDER

Original capacity (sheets)	100
----------------------------	-----

DOCUMENT FILING

Document filing (Standard / Option)	OPT
Document filing capacity- main and custom folders (pages)	20.000
Document filing capacity- quick file folder (pages)	10.000
Stored jobs	Copy, print, scan, fax transmission
Storage folders	Quick file folder, main folder, custom folder (max. 1000)
Confidential storage	•

FAX

Fax (Standard / Option)	OPT
Compression method	MH / MR / MMR / JBIG
Communication protocol	Super G3
Transmission time (sec)	2
Modem Speed (bps)	33.600 - 2.400
Transmission resolution	203,2 x 97,8, 406,4 x 391
Document Size (Min)	A5
Document Size (Max)	A3
Memory (MB)	1024
Grey Scale levels	256
Dial Registration; rapid/speed dial	2000
Broadcast Transmission (max. destinations)	500

WIRELESS LAN

Wireless LAN (Standard / Option)	OPT
Compliant regulation	IEEE802.11n / g / b
Access mode	Infrastructure mode, Software AP mode
Security	WEP, WPA / WPA2-mixed PSK, WPA / WPA2-mixed EAP, WPA2 PSK, WPA2 EAP

COPIER

Original paper size (Max.)	A3
First copy out time B/W (sec.)	4,5
E-sort Std	•
Continuous copy (Max. copies)	9999
Resolution Scan B/W (dpi)	600 x 600, 600 x 400
Resolution Scan Colour (dpi)	600 x 600
Resolution Print (dpi)	600 x 600
Gradation (equivalent levels) - B/W	2
Gradation (equivalent levels) - Colour	256
Zoom range (%)	25 - 400
Preset copy ratios	10

SCANNER

Network Scanner (Standard / Option)	STD
Scan method Push scan and Pull scan	•
Resolution push scan (dpi)	100, 150, 200, 300, 400, 600
Resolution pull scan (dpi)	75, 100, 150, 200, 300, 400, 600, 50 - 9600
File formats	STD TIFF, PDF, PDF / A-1b, encrypted PDF, JPEG, XPS OPT PDF / A-1a, compact PDF, searchable PDF, Microsoft Office (pptx, xlsx, docx), text (TXT), rich text (RTF)
Scan destinations Desktop	•
Scan destination FTP, Email	•
Scan destination Network folder	•
Scan destination USB memory	•

PRINTER

Resolution (dpi)	600 x 600, 9,600 x 600
Network Printer (Standard / Option)	STD
Interface Std/Opt	STD USB 2.0, 10Base-T / 100Base-TX / 1000Base-T OPT Secondary LAN support
Supported OS Standard	Windows 8.1, 10, Windows Server 2012, 2012R2, 2016, 2019.
Supported OS Options	Mac OS X 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15
Network protocols	TCP / IP (IPv4, IPv6)
Printing protocols	LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP, SMB, WSD
PDL Std/Opt	STD PCL 6 emulation, OPT Genuine Adobe PostScript 3
Available fonts	80 (PCL), 139 (Genuine Adobe PostScript 3)

FINISHING

Output Capacity Max.	500 - 3000
Staple Capacity (sheets) Max.	65
Saddle Stitch	OPT
Off-set shifting	STD
Hole punch	OPT

TONER YIELD

Black (pages at 6% coverage)	40000
------------------------------	-------

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett-Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation October 2019. Ref: MX-M4051 Datasheet. All trademarks acknowledged. E&O.