



bizhub אולם Black & White A3 multifunctional





Giving Shape to Ideas

CUSTOMER BENEFITS



Security Secure network integration, data encryption, hard drive overwrite, and advanced user authentication

1 ENHANCED FEATURES

PDF enhancements

OCR text recognition LK-105v4

Barcode fonts LK-106

Unicode fonts

LK-108

Antivirus LK-116

FOIP activation LK-117

OCR A and B fonts

ThinPrint[®] client

Document converter pack

Serverless pull printing LK-114 Trusted Platform Module LK-115v2

OPTIONS



Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability Numerous eco features reduce energy consumption and costs

٠

5




Intuitive operability Operate the bizhub like a smartphone or tablet with fully customised user interface

- -

(4)




Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive applications portfolio Services Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup






4 MEDIA INPUT	J
Intelligent media sensor IM-102	Í
1 x Universal tray PC-116	
2 x Universal tray PC-216	DF
Large capacity tray PC-416	DF
Large capacity tray PC-417)F
Copier desk DK-516x	DF
Large Capacity tray LU-302	
Banner tray BT-C1e	



LEGEND Mandatory option Option This option can only be installed with the respective option above it

FINISHING FUNCTIONALITIES



DESCRIPTION

ENHANCED FEATURES

LK-102v3 PDF enhancements	PDF/A(1b), PDF encryption, digital signature
LK-105v4 OCR text recognition	Searchable PDF and PPTX
LK-106 Barcode fonts	Supports native barcode printing
LK-107 Unicode fonts	Supports native Unicode printing
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110v2 Document converter pack	Generates various file formats incl. DOCX, XLSX and PDF/A
LK-111 ThinPrint [®] client	Print data compression for reduced network impact
LK-114 Serverless pull printing	Secure and Follow Me printing solution requiring no server
	application
LK-115v2 Trusted Platform Module	Trusted Platform Module for protection of data encryption and
	decryption
LK-116 Antivirus	Bitdefender® antivirus provides real time scanning of all incom-
	ing and outgoing data
LK-117 FOIP activation	Fax over IP networks (T.38), requires fax kit

CONNECTIVITY

EK-608 USB I/F kit	USB keyboard connection
MK-735 Mount kit	Installation kit for ID card reader
ID card reader	Various ID card technologies
AU-102 Biometric authentication	Finger vein scanner
FK-514 Fax board	Super G3 fax, digital fax functionality
EK-609 USB I/F kit	USB keyboard connection; Bluetooth
UK-221 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode

OTHERS

DF-632 Document feeder
DF-714 Document feeder

Reversing automatic document feeder, capacity 100 originals Dualscan automatic document feeder, capacity 100 originals

OTHERS	
OC-511 Original Cover	Cover instead of ADF
WT-506 Working table	Authentication device placement
KP-102 10-Key pad	For use instead of touchscreen
SC-509 Security kit	Copy guard function
EM-908 Replacement SSD	1 TB SSD to increase storage space
CU-102 Air cleaning unit	Improving indoor air quality by reduced emission
KH-102 Keyboard holder	To place USB keyboard
MEDIA INPUT	
IM-102 Intelligent media sensor	Autodetects paper weight and type
PC-116 1x Universal tray	500 sheets, A5-A3, 52-256 g/m ²
PC-216 2x Universal tray	2x 500 sheets, A5-A3, 52-256 g/m ²
PC-416 Large capacity tray	2,500 sheets, A4, 52–256 g/m ²

1,500 + 1,000 sheets, A5–A4, 52–256 g/m²

3,000 sheets, A4, 52-256 g/m²

BT-C1e Banner tray	Multipage banner feeding
DK-516x Copier desk	Provides storage space for print media and other materials
MEDIA OUTPUT	
FS-539 Staple finisher	50 sheets stapling; 3,200 sheets max. output
FS-539SD Booklet finisher	50 sheets stapling; 20 sheets booklet finisher;
	2,200 sheets max. output
PK-524 Punch kit for FS-539/SD	2/4 hole punching; autoswitching
RU-513 Relay unit	For FS-539/SD installation
JS-506 Job separator	Separation of fax output; etc.
FS-533 Inner finisher	50-sheet stapling, 500 sheets max. output
PK-519 Punch kit for FS-533	2/4 hole punching, autoswitching

PC-417 Large capacity tray LU-302 Large capacity tray

TECHNICAL SPECIFICATIONS

System speed A4	Up to 36 ppm
System speed A3	Up to 18 ppm
Autoduplex speed A4	Up to 36 ppm
1st page out time A4	4.6 sec.
Warm-up time	Approx. 12 sec. ¹
Imaging technology	Laser
Toner technology	Simitri [®] HD polymerised toner
Panel size/resolution	10.1" / 1024 x 600
System memory	8,192 MB (standard/max)
System hard drive	256 GB SSD (standard) / 1 TB SSD (optional)
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;
	Wi-Fi 802.11 b/g/n/ac (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S)
Automatic document feeder	Up to 100 originals; A6–A3; 35–163 g/m ² ;
(optional)	RADF or Dualscan ADF available
ADF double feed detection	Standard (with dualscan ADF)
Printable paper size	A6-SRA3; banner paper max. 1,200 x 297 mm;
	customized paper sizes
Printable paper weight	52-300 g/m ²
Paper input capacity	1,150 sheets / 6,650 sheets (standard/max)
Paper tray input (standard)	1x 500; A6–A3; custom sizes; 52–256 g/m ²
	1x 500; A5-SRA3; custom sizes; 52-256 g/m ²
Paper tray input (optional)	1x 500 sheets; A5-A3; 52-256 g/m ²
	2x 500 sheets; A5–A3; 52–256 g/m ²
	1x 2,500 sheets; A4; 52-256 g/m ²
	1x 1,500 + 1x 1,000 sheets; A5-A3; 52-256 g/m ²
Large capacity tray (optional)	1x 3,000; A4; 52-256 g/m ²
Manual bypass	150 sheets; A6–SRA3; custom sizes, banner; 60–300 g/m ²
Finishing modes (optional)	Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold

Letter-fold; Booklet

SYSTEM SPECIFICATIONS A6-SRA3; 52-256 g/m² Automatic duplexing Output capacity Up to 250 sheets / up to 3,300 sheets (standard/max) Stapling Max. 50 sheets or 48 sheets + 2 cover sheets (up to 209 g/m^2) Stapling output capacity Max. 100 sets Letter fold Max. 3 sheets Letter fold capacity Max. 30 sets; unlimited (without tray) Booklet Max. 20 sheets or 19 sheets + 1 cover sheet (up to 209 g/m^2) Booklet output capacity Max. 20 booklets; unlimited (without tray) Duty cycle (monthly) Rec. 33,000 pages; Max.² 175,000 pages Toner lifetime Black up to 25,000 pages Imaging unit lifetime Black up to 245,000/1,000,000 pages (drum/developer) 220-240 V / 50/60 Hz; Less than 1.58 kW Power consumption System dimension (W x D x H) 615 x 688 x 779 mm (without options) System weight Approx. 76.0 kg (without options) PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating systems	Windows 7 (32/64); Windows 8.1 (32/64); Windows 10 (32/64);
	Windows Server 2008 (32/64); Windows Server 2008 R2;
	Windows Server 2012; Windows Server 2012 R2; Windows Server
	2016; Windows Server 2019; Macintosh OS X 10.10 or later; Linux
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	Konica Minolta Print Service (Android);
	Konica Minolta Mobile Print (iOS/Android);
	AirPrint (iOS),Mopria (Android)
	optional: WiFi Direct

SCANNER SPECIFICATIONS

4

Scan speed	Up to 100/100 ipm in simplex (mono/colour)
	Up to 200/200 ipm in duplex (mono/colour)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);
	Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; Scan-
	to-DPWS; Scan-to-URL; TWAIN scan
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; Compact
	XPS; PPTX
	optional: Searchable PDF; PDF/A 1a and 1b; Searchable DOCX/
	PPTX/XLSX
Scan destinations	2,000 destinations + 100 groups; LDAP support

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max. A3
Magnification	25-400% in 0.1% steps; Auto-zooming

FAX SPECIFCIATION

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,000 single + 100 groups

USER BOX SPECIFICATIONS

Storable documents	Up to 3,000 documents or 10,000 pages
Type of user boxes	Public; Personal (with password or authentication); Group (with
	authentication)
Type of system boxes	Secure print; Encrypted PDF print; Fax receipt; Fax polling

SYSTEM FEATURES	
Security	ISO 15408 HCD-PP Common Criteria (in evalutation); IP filtering
	and port blocking; SSL3 and TLS1.0/1.1/1.2 network communication
	tion; IPsec support; IEEE 802.1x support; User authentication;
	Authentication log; Secure print; Kerberos; Hard drive overwrite;
	Hard drive data encryption (AES 256); Confidential fax; Print use
	data encryption
	optional: Antivirus realtime scanning (Bitdefender $^{\textcircled{B}}$); Copy
	protection (Copy Guard, Password Copy)
Accounting	Up to 1,000 user accounts; Active Directory support (user name
	password + e-mail + smb folder); User function access definition;
	Authentication by mobile device (Android)
	optional: Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (iOS)
Software	Net Care Device Manager; Data Administrator; Box Operator;
	Web Connection; Print Status Notifier; Driver Packaging Utility;
	Log Management Utility

¹ Warm-up time may vary depending on the operating environment and usage

- ² If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed
- All specifications refer to A4-size paper of 80 g/m² quality.
 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations. - The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
- particular page size (6% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.





