BP-20C20

A3 colour MFP that supports the small office environment



- Entry level 20ppm full colour A3 MFPs with 600 x 600 dpi print resolution
- Full-colour network scanning with multiple scan destinations
- Red and green LEDs to notify users of machine/job status from a dictage.
- 100-sheet Reversing Single Pass Feeder scans documents at up to $37 \mathrm{ipm^{\star 2}}$
- Sharpdesk Mobile print application*3 enables files on a mobile device to be printed
- Direct printing of PDF/TIFF/JPEG files

- Compact, cubic design with the smallest A3 device footprint*1 in the market
- Tiltable control panel with 4-inch, 5-line mono LCD
- Standard paper tray, as well as multi bypass tray, accommodates a wide variety of paper sizes, including A6 and A3W
- USB port conveniently located at the front of the MFP allowing easy printing from or scanning to the USB drive
- Optional wireless connectivity enables easy access from mobile devices and flexible MFP placement
- ID Card Copy function with dedicated key enables easy copying of both sides of a card onto a single page



^{*}¹ 'Footprint' refers to the floor or desk space occupied by the device for A3 colour laser MFPs at the time of publishing. *² Images per minute; when feeding A4 one-sided sheets. *³ Availability varies by country/region.

Specifications

Engine speed Colour ppm (A4) 20 Engine speed B/W ppm (A4) 20 Engine speed Colour ppm (A3) 12 Engine speed B/W ppm (A3) 12 Paper size: Min.-Max. A6 - A3W Paper weight (g/m2) 60 - 256 Paper capacity:Std (sheets) 350 Paper capacity: Max. (sheets) 1850 Warm Up Time (sec.) 29 Memory general min/max (GB) Duplex STD

Power requirements - rated local AC voltage

(Hz)

Power consumption (kW) 1.84

Dimensions (mm) 560 x 560 x 653 52

220 - 240V, 50 / 60Hz

Weight (kg)

SCANNER

Resolution (dpi) 600 x 600

FAX

Compression method MH / MR / MMR / JBIG **Communication protocol** Super G3 / G3 33600 - 2400 Modem Speed (bps) Document Size (Max) А3

TONER YIELD

Black (pages at 5% coverage) 18000 Cyan (pages at 5% coverage) 10000 Magenta (pages at 5% coverage) 10000 Yellow (pages at 5% coverage) 10000

Original paper size (Max.) А3 First copy out time B/W (sec.) 8.0 E-sort STD Continuous copy (Max. copies) 999

Resolution Scan (dpi) 600 x 600, 600 x 400

Resolution Print (dpi) 600 x 600 Gradation (equivalent levels) - B/W 256 Zoom range (%) 25 - 400 Preset copy ratios 10

PRINTER

Resolution (dpi) 600 x 600

USB 2.0, 10Base-T / 100Base-TX / Interface

1000Base-T

Supported OS STD: Windows 8.1, 10. Windows

Server 2012, 2012R2, 2016, 2019. OPT: Mac OS X 10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13, 10.14,

10.15

PDL emulation printer Std/Opt STD: PCL6 OPT: PostScript 3

emulation

WIRELESS LAN

Wireless LAN (Standard / Option) OPT

Compliant regulation IEEE802.11n/g/b Access mode

Infrastructure mode, Software AP

mode

Security WEP, WPA / WPA2-mixed PSK, WPA

/ WPA2-mixed EAP, WPA2 PSK,

WPA2 EAP

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Mac is a trademark of Apple inc. registered in the US and/or other countries. PCL is a registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. PCL is a registered trademark of Hewlett-Packard Company. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation May 2019. Ref:BP-20C25 Datasheet. All trademarks acknowledged. E&OE.

